



SILVER ARROW ENGINE FLUSH

Product Description:

Silver Arrow Engine Flush is manufactured by using a combination of carefully selected additive, solvent and mineral base stock.

The low viscosity of the Silver Arrow Flush Oil achieved by its sufficient solvent content allows the rapid circulation throughout the system with minimum pressure, leading to the most efficient removal of the contaminants within the shortest period.

While flushing the system rapidly, the high performance dispersant-type additive incorporated in the Engine Flush starts bonding, suspending and carrying the metallic particles, sludge carbon residue and other contaminants away from the system. With the additional help from the solvency provided by the solvent, Silver Arrow Engine Flush can effectively clean the whole crankcase even in a small quantity therefore, keeps the whole system clean before the next fill.

Pour Silver Arrow Engine Flush into the crankcase. Run the engine idly for 10-15 minutes. Drain out the waste oil.

Applications / Benefits:

- ▣ Low viscosity, high efficiency.
- ▣ Removes timely built deposits, grime and carbon in the system.
- ▣ One small can for whole crankcase flushing.
- ▣ Reduce the maintenance cost.

Typical Characteristics:

Test Description	Method	
Specific Gravity @ 15 °C	ASTM D 4052	0.837
Flash Point, °C	ASTM D 92	98
Pour Point, °C	ASTM D 97	-24
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	11.02
TBN, mgKOH/g	ASTM D 2896	1.1
Color	ASTM D 1500	Slightly Red